



2" 2.8/18mm	2"	APS-C	4/3"
FOCAL LENGTH	f=18mm		
F-NUMBER	F=2.8-16		
PICTURE SIZE	25.6x19.6mm	22.3x16.7mm	18.4x13.8mm
ANGLE OF VIEW (°)	VER. ANGLE	56.1°	49.7°
	HOR. ANGLE	70.5°	63.4°
	DIA. ANGLE	81.8°	74.8°
DISTORTION (TV)	1.25%	0.44%	-0.05%
FIELD OF VIEW (MINIMUM FOCUS DISTANCE)	VER.	128mm	111mm
	HOR.	172mm	149mm
	DIA.	213mm	187mm
MINIMUM FOCUS DISTANCE	0.1m		
FLANGE BACK	17.526mm in air		
BACK FOCUS	15.5mm in air		
FILTER SCREW SIZE	M77x0.75		
FRONT/REAR EFFECTIVE DIA.	FRONT ϕ 55.0mm		REAR ϕ 25.4mm
MOUNT	M35x0.75		
EXIT PUPIL	-65.1mm		
TEMPERATURE RANGE	-10~+50 °C		
STORAGE TEMPERATURE RANGE	-20~+60 °C		
RESOLUTION CENTER/CORNER	CENTER 160lp/mm		CORNER 100lp/mm
WEIGHT	460g		

NOTE: Specifications and availability are subject to change without notice

注) 本仕様については、予告なしに変更する場合があります。



		尺度	1/1	工場番号	LM18VM35
		機種名	2" F2.8 / f=18mm		
		機種番	LM18VM35		
2020.12.8	作成年月日				S10-680



MACHINE VISION SHOP

FOR ALL YOUR VISION PRODUCTS

Thank you for downloading this document from
www.machine-vision-shop.com

If you have any questions, you need help composing the right package for your application or do you want to order?

Feel free to contact us via e-mail at
sales@vision-consultancy.nl or visit our webshop.

Our vision experts are happy to help you.



Natascha Overhof



Christian Cromptoets



Machine Vision Shop

Trade name of Vision Consultancy BV

Robert Schumandomein 2
6229 ES Maastricht
The Netherlands

+31 (0) 438 522 651

sales@vision-consultancy.nl
www.machine-vision-shop.com

Scan me to visit
[machine-vision-shop](http://machine-vision-shop.com)

