




●Modulation Transfer Function (MTF)




4D-0630T0240


●Distortion (歪曲収差)



●Vignetting (周辺光量)



●Spectral Transmittance (分光透過率)



●Resolving Power (解像力)

y	0	4.76	6.35	7.94		
Rr(S)		32	40	32		
Rt(M)	100	40	32	32		

●Entrance Pupil Position (入射瞳位置)

-12.02 [mm] *

●Exit Pupil Position (射出瞳位置)

-17.83 [mm] *

●1st Principal Point (第一主点)

-22.07 [mm] *

●2nd Principal Point (第二主点)

-25.00 [mm] * (* : From Image Plane)

SPEC. INFO	FL-BC2518-VG RC SPEC.	3122530-S001-RC-B13
		Sep. 27, 2012

1. Model FL-BC2518-VG

2. Application For 1 Format Camera

3. Specification

3-1. Physical (As per the attached drawing)

- | | |
|-----------------------|--|
| (1) Dimensions | $\phi 42\text{mm} \times 40\text{ mm}$ |
| (2) Weight | 87g |
| (3) Mount | C-Mount (1 – 32 UN – 2A) |
| (4) Filter Screw Size | $\phi 40.5\text{ mm}$, P = 0.5 mm |

3-2. Optical

- | | |
|-----------------------------|----------------------------|
| (1) Focal Length | 25 mm $\pm 5\%$ |
| (2) Max. Aperture Ratio | 1: 1.8 |
| (3) Iris Range | F / 1.8 to F / 16 to Close |
| (4) Angle of View | Diagonal 34.79° |
| | Horizontal 28.24° |
| | Vertical 21.44° |
| (5) Picture format | 12.7 mm $\times$ 9.525 mm |
| (6) Minimum Object Distance | 0.6 m |
| (7) Back Focal Length | 15.80 mm |
| (8) Flange Back Length | 17.526 mm $\pm$ 0.05 mm |

3-3. Mechanical

- | | |
|------------------------|---|
| (1) Focusing Mechanism | Straight Helicoid |
| | Rotation Angle 163.3° |
| | Rotation Torque 0.98N·cm to 6.0 N·cm |
| | Focus Ring can be fixed at any positions by 3 fixing screws (A) or 1 thumb screw (refer to external view) |
| (2) Iris Mechanism | Non-click, Close-down |
| | Rotation Angle 96° |
| | Rotation Torque 0.98N·cm to 6.0 N·cm |
| | Iris Ring can be fixed at any positions by 3 fixing screws (B) or 1 thumb screw (refer to external view) |

3-4. Vibration & Shock Test Standard

(1) Vibration Conditions

Wave	Sine Wave
Acceleration	1.96 m/s ² to 59.78 m/s ²
Cycle Range	10 Hz to 55 Hz
Cycle Period	3 Minutes
Duration of Vibration	120 Minutes Respectively in Three Dimensional Directions

(2) Shock Conditions




Tester	Shock Testing Machine by Dropping
Impact Force	588 m/s ²
Duration of Shock	3.5 ms
Directions & Number of Times	1 Time Respectively in Three Dimensional Directions

SPEC. INFO	FL-BC2518-VG RC SPEC.	3122530-S001-RC-B23
		Sep. 27, 2012

3-5. Environmental Temperature Range -20°C to $+50^{\circ}\text{C}$

4. Accessories

(1) Front Lens Cap	1 piece	
(2) Rear Lens Cap	1 piece	
(3) Fixing Screw ① for Focus Ring	3 pieces	
(4) Fixing Screw ② for Iris Ring	3 pieces	
(5) Thumbscrew	2 pieces	(for Optional Usage)
(6) Packing Box	1 piece	



SPEC. INFO		FL-BC2518-VG
3122530-S001-RC-B33		
Sep.27.2012		
RICOH		



VISION CONSULTANCY
MAKING THE UNSEEN VISIBLE

Thank you for downloading this document from
www.machine-vision-shop.com

If you have any questions, you need help composing the
right package for your application or do you want to order?

Feel free to contact us via e-mail at sales@vision-consultancy.nl or visit our webshop.

Our vision experts are happy to help you.



Natascha Overhof



Christian Cromptoets



VISION CONSULTANCY

Robert Schumann domein 2
6229 ES Maastricht
The Netherlands

+31 (0) 438 522 651

sales@vision-consultancy.nl
www.machine-vision-shop.com

Scan me to visit
machine-vision-shop

