


ILLUMINATOR DATA-ID

CAS2-00-040-X-B-24V

Lighting Dimension



Mechanical Information	
Casing Material	Aluminium
Storage Temperature Range	Temp 0 - 45°C, Humidity 20-85%
Weight	360 g
Length / Outer Diameter	107.5 mm
Width / Inner Diameter	60 mm
Thickness / Height	66 mm



CAS2-00-040-X-B-24V

Optical Information						
Part Number		CAS2-00-040-X-B-24V				
LED Color			BLUE			
Wavelength	(nm)	470				
Intensity (±15%)	(Lux)	9380	7190	4310		
Working Distance	(mm)	20	30	50		
Illumination (number of row)			X			
Illumination Active Area	(
Active Length / Outer Diameter Active Width / Inner Diameter	(mm)	48				
Emission angle	(mm) (deg.)					
Eye Safety Class (IEC62471)	(deg.)) II				
Electrical Information						
Lighting Supply Voltage						
(constant voltage mode)		24V ± 2%				
Continuous Current	(mA)	350				
Power Consumption	(W)	8.4				
Lighting casing temperature,						
Operating after 60 minutes	°C	°C 63.2				
Strobe Mode Specification						
Pulse Operation		YES				
Max. Lighting Supply Voltage	(\/)	Pulsing at 24VDC to 48VDC, 0-10% Duty Cycle, Recommended at 36VDC				
(Constant voltage power supply)	(V)	Pulsing at 24VDC to 48VDC, 0-10% Duty Cycle, Recommended at 36VDC				
Pulse Current, (Max. 10msec)	(mA)	1050				
(Constant current power supply)	(IIIA)	1030				
Max. Trigger Pulse Duration	(msec)	10				
Duty Cycle	0-10%					
Additional Information						
Additional Cooling Method		Attached to machine part for better heat dissipation				
Intensity Controller Selection		ANG, ST, SD and SDA Series				
CE Conformity	YES					
RoHS Compliance	YES					
Connection						
Connector Type (Default):	, ,	JST SMR-03V				
Cable Length out from lighting:	(mm)	Di-	500	Cable Cala		
Pin Configuration :	<u> </u>	Pin 1	Signal LED +	Cable Color RED		
		<u>1</u> 2	N.C.			
		3	N.C. LED -	 WHITE		
		3	110	WITTE		
	1					
Application						
Illumination Type		Coaxial Illumination				
Applicattion Use		Surface inspection and alignment, wafer, metal surface, film, LCD and glass, pattern on PCB.				
	-	Tanana and and and and and an and an analy an analy an analy and an analy pattern on the an				



Thank you for downloading this document from www.machine-vision-shop.com

If you have any questions, you need help composing the right package for your application or do you want to order?

Feel free to contact us via e-mail at sales@vision-consultancy.nl or visit our webshop.

Our vision experts are happy to help you.



Natascha Overhof



Christian Crompvoets



VISION CONSULTANCY

Robert Schumandomein 2 6229 ES Maastricht The Netherlands

+31 (0) 438 522 651

sales@vision-consultancy.nl www.machine-vision-shop.com

