



Lighting Dimension







ROHS CE

Mechanical Information	
Casing Material	Aluminium
Storage Temperature Range	Temp 0-45°C, Humidity 20-85%
Weight	110 g
Length / Outer Diameter	56.4 mm
Width / Inner Diameter	10 mm
Thickness / Height	35 mm

ILLUMINATOR DATA-ID

DLR3-45-050-1-G-24V

TMS

Optical Information						
Part Number			DLR3-45-050-1-G-24V			
LED Color		GREEN				
Wavelength	(nm)		5 40			
Intensity (±15%)	(Lux)		TBA			
Working Distance	(mm)	5	10	14		
Illumination (number of row)			1			
Illumination Active Area						
Active Length / Outer Diameter	(mm)	44.4				
Active Width / Inner Diameter	(mm)	12				
Emission angle	(deg.)	45				
Eye Safety Class (IEC62471)		EXEMPT				
Electrical Information						
Lighting Supply Voltage						
(constant voltage mode)			24V ± 2%			
Continuous Current	(mA)	24V ± 270 120				
Power Consumption	(W)	2.88				
Lighting casing temperature,	,	2.00				
Operating after 60 minutes	°c	52				
Strobe Mode Specification						
Pulse Operation		YES				
Max. Lighting Supply Voltage		Pulsing at 24VDC to 48VDC, 0-10% Duty Cycle				
(Constant voltage power supply)	(∨)	Recommended at 36VDC				
Pulse Current, (Max. 10msec) (Constant current power supply)	(mA)	360				
Max. Trigger Pulse Duration	(msec)	10				
Duty Cycle	(msec)	10 0-10%				
			0-10%			
Additional Information						
Additional Cooling Method		Attached to machine part for better heat dissipation				
Intensity Controller Selection		ANG, ST, SD and SDA Series				
CE Conformity		YES				
RoHS Compliance		YES				
			120			
Connection						
Connector Type (Default):		JST SMR-03V				
Cable Length out from lighting :	(mm)		500			
Pin Configuration :		Pin	Signal	Cable Color		
		1	LED +	RED		
		2	N.C.			
		3	LED -	WHITE		
Application						
Illumination Type		Diffused Illumination				
Applicattion Use		Character recognition on shining surface, lead inspection				
P.P						



Thank you for downloading this document from www.machine-vision-shop.com

If you have any questions, you need help composing the right package for your application or do you want to order?

Feel free to contact us via e-mail at sales@visionconsultancy.nl or visit our webshop.

Our vision experts are happy to help you.



Natascha Overhof



Christian Crompvoets



VISION CONSULTANCY

Robert Schumandomein 2 6229 ES Maastricht The Netherlands

+31 (0) 438 522 651

sales@vision-consultancy.nl www.machine-vision-shop.com Scan me to visit machine-vision-shop

