


# **ILLUMINATOR DATA-ID**

### LSW-30-070-3-R-24V

#### **Lighting Dimension**



Mechanical Information	
Casing Material	Aluminium
Storage Temperature Range	Temp 0 - 45°C, Humidity 20-85%
Weight	120 g
Length / Outer Diameter	70 mm
Width / Inner Diameter	32 mm
Thickness / Height	20 mm



## LSW-30-070-3-R-24V

Optical Information						
Part Number			LCW 20 070 2 D 24V			
LED Color			LSW-30-070-3-R-24V RED			
Wavelength	(nm)					
		630				
Intensity (±15%) Working Distance	(Lux)	99800 37	83500 42	68000 47		
Illumination (number of row)	(mm)	37	3	4/		
Illumination (number of row)			3			
	(	63				
Active Length / Outer Diameter Active Width / Inner Diameter	(mm) (mm)	34.7				
		34.7				
Emission angle Eye Safety Class ( IEC62471 )	(deg.)	EXEMPT				
2,0 30.00, 0.000 ( 1.002 1.7 )	<b>,</b>		e.c.m.			
Electrical Information						
Lighting Supply Voltage						
(constant voltage mode)			24V ± 2%			
Continuous Current	(mA)	180				
Power Consumption	(W)	4.32				
Lighting casing temperature,						
Operating after 60 minutes	°C	52.1				
Strobe Mode Specification						
Pulse Operation		YES				
Max. Lighting Supply Voltage						
(Constant voltage power supply)	(V)	Pulsing at 24VDC to 48VDC, 0-10% Duty Cycle, Recommended at 36VDC				
Pulse Current, (Max. 10msec)						
(Constant current power supply)	(mA)	540				
Max. Trigger Pulse Duration	(msec)	10				
Duty Cycle	(msec)	(msec) 10 0-10%				
outy cycle	<u> </u>		0.1070			
Additional Information						
Additional Cooling Method		Attached to machine part for better heat dissipation				
Intensity Controller Selection		ANG, ST, SD and SDA Series				
CE Conformity		YES				
RoHS Compliance		YES				
Connection						
Connector Type (Default):		JST SMR-03V				
Cable Length out from lighting :	(mm)	•	500			
Pin Configuration :		Pin	Signal	Cable Color		
		1	LED+	RED		
		2	N.C.			
		3	LED -	WHITE		
Application						
Illumination Type		Direct Illumination				
Applicattion Use		Substrate inspection, label inspection, flat surface, fiducially recognition.				
application ose		Substrate inspection, label inspection, flat surface, floucially recognition.				



Thank you for downloading this document from www.machine-vision-shop.com

If you have any questions, you need help composing the right package for your application or do you want to order?

Feel free to contact us via e-mail at sales@vision-consultancy.nl or visit our webshop.

Our vision experts are happy to help you.



Natascha Overhof



Christian Crompvoets



#### **VISION** CONSULTANCY

Robert Schumandomein 2 6229 ES Maastricht The Netherlands

+31 (0) 438 522 651

sales@vision-consultancy.nl www.machine-vision-shop.com

